

FREEDOM

Communications System Analyzer

R8100



DATA SHEET

Table of Contents

Operating/Display Modes	3
General	3
Generator (Receiver Test)	4
Receiver (Transmitter Test)	5
Spectrum Analyzer	6
Oscilloscope	7
Audio Modulation Synthesizer	7
Tracking Generator	7
Digital Voltmeter (DVM)	7
Timebase	7
Display	7
Supplemental Digital Specifications	8
Remote Interface (Optional Feature)	8

Operating/Display Modes

- AM/FM Duplex Monitor and Generator
- Audio Synthesizer
- Tracking Generator (Opt.)
- Dual Display (Opt.)
- Cable Fault Locator (Opt.)
- Spectrum Analyzer
- Frequency Counter
- Frequency Error Meter
- Digital Voltmeter
- Power Meter
- Oscilloscope
- Signal Strength Meter
- SINAD/Distortion Meter



General

Displayed Average Noise:

Level (DANL):	-140dBm (50 Ohm input termination)
Dynamic Range:	80dB
Input Related Spurious:	-60dBc max
Residual Spurious (non-input related):	-70dBm

Power

DC Power Requirements:	15-16VDC @ 8.0A max
AC Adapter Specs:	100-240VAC, 2.5A max, 50-60Hz
Battery Power:	Internal Battery
Battery Operation:	1.5 hour typical easily swappable for extended operation

MECHANICAL/ENVIRONMENTAL

Weight:	13.75 lbs including internal battery 6.24kg)
Dimensions:	9.4" (23.9cm) H, 12.7" (32.3cm) W, 7.5" (19.1cm) D
Operating Altitude:	Up to 15,000 ft (4572 m)
Humidity:	80% maximum relative humidity
Operating Temperature:	-20° to 50°C with external DC; 0° to 50°C using supplied AC adapter
Storage Temperature:	Without battery: -30° to +80°C; With battery: -20° to +50°C
Battery Charging Temperature:	0° to +45°C
Shock and Vibration Rating:	MIL-PRF-28800F, Class 3

WARRANTY

Standard Warranty:	Two years
Three Year Service Plan:	Optional
Five Year Service Plan:	Optional

Generator (Receiver Test)

Port Protection Limit	5W for 30 seconds
Frequency Range:	1MHz to 1GHz (250kHz to 1GHz typical); Optional to 3GHz
Extended Frequency Range (Optional):	1MHz to 3GHz (250kHz to 3GHz typical)
Frequency Resolution:	1Hz

OUTPUT LEVEL GENERATE PORT

Range FM:	+5dBm to -95dBm below 2GHz; -5dBm to -95dBm above 2GHz
Range AM:	-1dBm to -95dBm below 2GHz; -11dBm to -95dBm above 2GHz
Resolution:	0.1dB
Accuracy:	±2dB

OUTPUT LEVEL RF I/O PORT

Range FM:	-30dBm to -130dBm below 2GHz; -40dBm to -130dBm above 2GHz
Range AM:	-36dBm to -130dBm below 2GHz; -46dBm to -130dBm above 2GHz
Resolution:	0.1dB
Accuracy:	±1dB to 1GHz ; ±2dB > 1GHz

SPECTRAL PURITY

Harmonic Spurious:	-20dBc max
Non-Harmonic Spurious:	-35dBc max; <-30dBc at mixing product frequencies (3227MHz - Carrier)
Residual FM:	4Hz, 300Hz to 3kHz (<1GHz); 5Hz, 300Hz to 3 kHz (> 1GHz)
Residual AM:	1.0% max, 300Hz to 3kHz
SSB Phase Noise (20 kHz Offset):	-95dBc/Hz max below 1GHz (15° to 35°C); -93dBc/Hz max all frequencies (0° to 50°C)

FM MODULATION

Deviation Range:	0 to 75kHz
Deviation Resolution:	1 Hz
Deviation Accuracy:	5% of setting
RF Output Frequency Range:	0 to 40 kHz
Modulation Output Frequency Range :	0 to 20kHz
RF Output Modulation Bandwidth:	DC to 100 kHz
Modulation Output Bandwidth:	5 Hz to 20kHz
IF Bandwidth:	> 200 kHz
Pre-emphasis:	750 µs (selectable)
Total Harmonic Distortion:	1% (1 kHz rate, 6 kHz Deviation FM, 300 Hz to 3 kHz Audio BW)

AM MODULATION

Deviation Range:	0 to 90% (AM Depth)
Deviation Resolution:	1%
Deviation Accuracy:	5% of setting
RF Output Modulation Frequency Range:	0 to 40 kHz
Modulation Output Frequency Range:	0 to 20 kHz
RF Output Bandwidth:	DC to 100 kHz
Modulation Output Bandwidth:	5 Hz to 20kHz
IF Bandwidth:	> 200 kHz
Total Harmonic Distortion:	1% (1 kHz rate, 10 % to 85 % AM, 300 Hz to 3 kHz Audio BW)

SSB-AM (USB or LSB) Modulation

AM Depth Range:	0 to 90%
Depth Resolution:	1%
Modulation Bandwidth:	300Hz to 20kHz

Receiver (Transmitter Test)

Frequency Range:	250kHz – 1GHz (3GHz optional)
------------------	-------------------------------

SENSITIVITY

Narrowband FM:	2.0uV for 10dB EIA SINAD
Wideband FM:	10uV for 10dB EIA SINAD
AM:	10uV for 10dB EIA SINAD

RF I/O PORT

VSWR:	< 1.2 to 2GHz, ~ 1.5 to 3GHz
Max Power:	50W for 5 minutes 150W for 30 seconds (30 sec. on, 5 min. off)
Absolute Max Power:	150W
Alarm:	Internal temperature alarm

ANTENNA PORT

Maximum Power:	0dBm
Alarm:	+10dBm

IF FILTERS:

6.25kHz, 12.5kHz, 25kHz, 50kHz, 100kHz, 200kHz

FREQUENCY ERROR MEASUREMENT

Type of Display:	Autoranging
Resolution:	1Hz

FM DEVIATION MEASUREMENT

Demodulation Range:	Up to ± 75 kHz
Accuracy:	$\pm 5\%$ plus residual FM
Frequency Response:	Selectable per the following: Low Pass Filters: 300Hz, 3kHz, 20kHz High Pass Filters: 1Hz, 300Hz, 3kHz

DEMOD HARWARE CHARACTERISTICS

Demodulation Output Level:	6.25kHz B/W: 2.56V / 1kHz 12.5kHz B/W: 1.28V / 1kHz 25kHz B/W: 0.64V / 1kHz 50kHz B/W: 0.32V / 1kHz 100kHz B/W: 1.6V / 10kHz 200kHz B/W: 0.8V / 10kHz
Demodulation Output Amplitude Flatness:	± 0.2 dB (300Hz to 3kHz), 1dB point @ 20kHz
Demodulation Output Impedance:	100 ohms nominal

AUDIO WEIGHTING FILTERS

Filters: none, C-message, CCITT	none, C-message, CCITT
De-emphasis (selectable):	750's

AM MODULATION MEASUREMENTS

Demodulation Range:	0 to 100%
Accuracy:	$\pm 5\%$ for levels below 80%
Frequency Response:	Selectable per the following:
Demodulation Output Level:	Low Pass Filters: 300Hz, 3kHz, 20kHz High Pass Filters: 1Hz, 300Hz, 3kHz
Demodulation Output Amplitude Flatness:	0.8V peak per 10% AM Modulation
Output Impedance:	± 0.2 dB (300Hz to 3kHz), 1dB point @ 20kHz 100 ohms nominal
SSB Sideband Suppression:	>70 dB

RECEIVE SIGNAL STRENGTH LEVEL METER

Frequency Range:	1MHz to 1GHz (250kHz to 1GHz typical); Optional to 3GHz
Accuracy:	± 2 dB
Sensitivity:	-120dBm (Antenna Port; Preamplifier on; 6.25kHz IF B/W)

BROADBAND POWER METER (RF In/Out Port)

Frequency Range:	1MHz to 1GHz (250kHz to 1GHz typical); Optional to 3GHz
Measurement Range:	0.1W to 150W
Input Impedance:	50 Ohms
Accuracy:	$\pm 10\%$ (2 KHz - 1GHz); $\pm 10\%$ (1GHz - 3GHz <2.5W)
Protection:	Over temperature alarms

FREQUENCY COUNTER

Frequency Range:	5Hz to 100kHz
Period Counter Range:	5Hz to 20kHz
Input Level:	0.1V rms min

SINAD METER

Accuracy:	$\pm 1\text{dB}$ @ 12dB SINAD
Input Level:	0.1V rms min
Frequency Range:	300 Hz to 10kHz
Reading Range:	0 to >60 dB
Resolution:	0.01dB

DISTORTION METER

Reading Range:	0.00% to 100%
Distortion Accuracy:	The greater of: $\pm 0.5\%$ of distortion or $\pm 10\%$ of reading
Input Level:	0.1V rms min
Frequency Range:	300Hz to 10kHz
Resolution:	0.01%

OPTIONAL MODES

DMR (MOTOTRBO™), dPMR, NDXN (Conventional and Type-C Trunking)
P25 Phase 1 (Conventional and Trunking), P25 Phase 2, PTC (ITCR), TETRA

Spectrum Analyzer

SWEEP

Frequency Range:	1MHz to 1GHz (250kHz to 1GHz typical); Optional to 3GHz
Frequency Resolution:	1Hz
Span Accuracy:	5%
Update Rate:	~10 times per second (depending on span)

AMPLITUDE

Level Accuracy:	$\pm 2\text{ dB}$
Scales (dB/div):	10 (1, 2, & 5 w/ESA option)
Log Linearity Accuracy:	<0.1dB
Reference Level Resolution:	1dB
Reference Level Range:	+60 to -70dB
T/R Port Dynamic Range:	80dB
Typical Noise Floor Performance:	-140dBm
SSB Phase Noise (20 kHz Offset):	-95dBc/Hz max below 1GHz (15° to 35° C) -93dBc/Hz max all frequencies (0° to 50° C)
Resolution Bandwidth	Auto Selected
Harmonic Spurious (Antenna Port, No Attenuation):	-20dBc max
Non-Harmonic Spurious (Antenna Port, No Attenuation):	-60dBc max
Residual Spurious (Input Terminated):	-70dBm
Markers:	Delta, Absolute, and Frequency
Modes:	Standard, Average, Freeze, Max Hold, and Peak Hold

Oscilloscope

VERTICAL INPUT

Input Impedance:	1 Meg Ohm / 600 Ohm (Selectable)
Range:	± 70 VDC, ± 33 Vrms AC / ± 24 VDC, ± 15 Vrms AC
Accuracy:	5% of full scale
Bandwidth:	0 to 50kHz

HORIZONTAL SWEEP

Range:	20 μ Sec to 1 Sec / div. (Selectable)
--------	---

TRIGGER SELECTION

Normal, Auto (Free Running), Single Sweep and Freeze

SPECIAL FUNCTIONS

Markers:	Absolute Voltage, Delta Voltage, Delta Frequency and Delta Period
----------	---

Audio Modulation Synthesizer

Modulation Types:	1 kHz tone, Standard formats (Private Line, Digital Private Line, DPL Invert, Two-Tone Paging, 5/6 Tone Paging, POCSAG, EURO Tones, or User Defined Tone Sequences), Tone-A, Tone B, Tone C (RF Output), DTMF, and external inputs from both a supplied microphone and BNC connector.
Modulation Output Level:	± 8 V peak (± 16 /BW V/kHz FM, ± 0.08 V/% AM)
Amplitude Flatness:	± 0.2 dB (300Hz to 3kHz), 1dB point @ 20kHz
1 kHz Tone Distortion:	Not to exceed 1% THD
Impedance:	100 Ohms
Modulation Input Level:	± 1 V peak reference
Amplitude Flatness:	± 0.2 dB (300Hz to 3kHz), 1dB point @ 20kHz
Impedance:	600 Ohms
Microphone Input Amplitude Flatness:	± 0.2 dB (300Hz to 3kHz), 1dB point @ 20kHz

Tracking Generator

Frequency Range:	1MHz to 1GHz (250kHz to 1GHz typical); Optional to 3GHz
------------------	---

Digital Voltmeter (DVM)

Input Impedance:	1 Meg Ohm / 600 Ohm (Selectable)
Voltage Range:	1V, 10V, 70V full scale
Frequency Range:	50Hz to 20kHz
DC Accuracy:	1% full scale ± 1 LSB
AC Accuracy:	5% full scale ± 1 LSB

Timebase

Output Frequency:	10MHz
Stability:	Aging: ± 0.1 ppm / year Temp.: ± 0.01 ppm
Output Level:	Minimum 0dBm into 50 Ohms
Warm Up:	3 minutes: within ± 0.1 ppm

Display

FRONT PANEL DISPLAY

Resolution:	800 x 600
Size:	Size: 8.4" (21.3cm) Full Color LCD

EXTERNAL DISPLAY

External Display:	VGA
-------------------	-----

REMOTE FRONT PANEL

Remote Front Panel:	Available over Ethernet
---------------------	-------------------------

Supplemental Digital Specifications

DMR

FSK ERROR

Range: 0 to 10%

Accuracy (2% to 10%): <5%

Resolution: 0.01%

MAGNITUDE ERROR

Range: 0-5%

Accuracy: <5% of reading

Resolution: 0.01%

SYMBOL DEVIATION

Range: 1500 to 2350Hz

Accuracy: ± 10 Hz

Resolution: .1Hz

BER

Range: 0 to 20%

Resolution: 0.00001%

NXDN

FSK ERROR

Range: 0 to 10%

Accuracy (2% to 10%): <5%

Resolution: 0.01%

MAGNITUDE ERROR

Range: 0-5%

Accuracy: <5% of reading

Resolution: 0.01%

SYMBOL DEVIATION

Range: 840 to 1260Hz (4800bps)
1920 to 2880Hz (9600bps)

Accuracy: ± 10 Hz

Resolution: .1Hz

BER

Range: 0 to 20%

Resolution: 0.00001%

dPMR

FSK ERROR

Range: 0 to 10%

Accuracy (2% to 10%): <5%

Resolution: 0.01%

MAGNITUDE ERROR

Range: 0-5%

Accuracy: <5% of reading

Resolution: 0.01%

SYMBOL DEVIATION

Range: 1500 to 2350Hz

Accuracy: ± 10 Hz

Resolution: .1Hz

BER

Range: 0 to 20%

Resolution: 0.00001%

TETRA

EVM (RMS)

Range: 0 to 20%

Accuracy (2% to 10%): <10%

Resolution: 0.10%

RESIDUAL CARRIER

Range: 0-10%

Accuracy: ± 0.1 %

Resolution: 0.10%

FREQUENCY ERROR

Accuracy: ± 500 Hz

Resolution: 1 Hz

P25 MEASUREMENT MODULATION FIDELITY

Range: 0 to 10%

Resolution: 0.01%

Accuracy: <5.0% of reading
for 2.0 % and higher

Remote Interface (Optional Feature)

REMOTE FRONT PANEL

Available over Ethernet

FREEDOM

Communication Technologies

2002 Synergy Blvd, Suite 200, Kilgore, Texas 75662

Toll Free Phone: (844)-90-FREEDOM or (844)-903-7333

Phone: 903-985-8999 Fax: 903-985-8998 Email: sales@freedomcte.com

Please visit our website at www.freedomcte.com

08 / Freedom / Communications System Analyzer R8100 / FCT-2036G



Complies With
UL 61010-1
CSA C22.2 No. 61010-1

All trademarks indicated as such herein are trademarks of Freedom Communication Technologies® Reg. U.S. Pat. & Tm. Off. MOTOTRBO is registered in the U.S. Patent and Trademark Office by Motorola, Inc. All other product or service names are the property of their respective owners. © 2017 Freedom Communication Technologies. All rights reserved. Freedom Communication Technologies reserves the right to make changes in its products and specifications at any time and without notice.