

# Enterprise 1300


SKU: 460149

## FEATURES

- Three outdoor antenna ports to target multiple carrier towers.
- Wired or LTE WilsonPro Cloud access for remote functionality.
- Up to 26 dBm in uplink power and 17 dBm in downlink power.
- XDR technology to virtually eliminate shutdown or signal loss.
- 4.3-inch LCD touchscreen for an enhanced user-experience.
- Works with ALL phones and cellular devices on ALL carriers.

\*⚠ **WARNING:** Cancer and Reproductive Harm - [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

## Kit Includes



Enterprise 1300  
or Enterprise 1300R  
Amplifier



Outside  
Directional Antenna  
(314411)



Inside Dome  
Antenna  
(304412)



Lightning Surge  
Protector  
(859902)




2 ft. Wilson400  
Cable  
(952402)



100ft Low-Loss  
Wilson400 Cable x2  
(952300)



## RACK MOUNT OPTION:



**Enterprise  
1300R**  
SKU: 460150

## About

The WilsonPro **Enterprise 1300/1300R** is a commercial-grade, in-building cellular amplifier that represents the latest in cell signal boosting technology—including a revolutionary industry-first, three outdoor-antenna-port configuration. Depending on cell tower locations, using up to three outdoor antennas (each dedicated to a specific frequency band to collectively amplify signals from multiple towers) helps maximize coverage in commercial spaces up to 40,000 sq. ft.\*

Based on user need or preference, the Enterprise 1300/1300R can also utilize “common mode” as a default; using only a single outdoor (donor) antenna and a single port to receive cell signal.

With wired or LTE access (using the built-in cellular modem) to the WilsonPro Cloud for remote functionality, the Enterprise 1300/1300R provides integrators and building managers with the capability to remotely manage, monitor, and adjust their amplifier, as well as receive real-time updates on a smartphone or tablet. Immediate notification of issues, such as system failure, oscillation, or change in signal strength is also provided via text or email.

The Enterprise 1300/1300R generates up to 26 dBm in uplink power—enabling it to reach towers at much greater distances. With up to 17 dBm in downlink power, it's also one of the most powerful amplifiers in its price range. The “R” model name signifies its rack-mount option.

This amplifier includes a 3-year manufacturer's warranty and a 30-day money-back guarantee.

\*Depending on outside signal conditions.

## Specifications

| MODEL NUMBER         | 460149* • 460150*                   |               |
|----------------------|-------------------------------------|---------------|
| FREQUENCIES          | Band 12/17                          | 700 MHz       |
|                      | Band 13                             | 700 MHz       |
|                      | Band 5                              | 850 MHz       |
|                      | Band 4                              | 1700/2100 MHz |
|                      | Band 25                             | 1900 MHz      |
| MAX GAIN             | 70 dB                               |               |
| MAX UPLINK POWER     | 26 dBm                              |               |
| MAX DOWNLINK POWER   | 17 dBm                              |               |
| IMPEDANCE            | 50 Ohm                              |               |
| POWER                | 110 - 240 V AC, 50 - 60 Hz, 30 W    |               |
| CONNECTORS           | N-Female                            |               |
| AMPLIFIER DIMENSIONS | 19 x 12 x 2.5 • 17.5 x 12 x 3.75 in |               |
| AMPLIFIER WEIGHT     | 16.515 lbs • 9.66 lbs               |               |

## Detailed Specifications

| 1300 / 1300R                                      |                                                                                            |               |        |         |         |
|---------------------------------------------------|--------------------------------------------------------------------------------------------|---------------|--------|---------|---------|
| SKU                                               | 460149 / 460150                                                                            |               |        |         |         |
| Model Number                                      | 460149 / 460150                                                                            |               |        |         |         |
| FCC ID                                            | PWO460049 / PWO460050                                                                      |               |        |         |         |
| Connectors                                        | N-Connectors                                                                               |               |        |         |         |
| Antenna Impedance                                 | 50 Ohms                                                                                    |               |        |         |         |
| Frequency                                         | 698-716 MHz, 729-746 MHz, 777-787 MHz, 824-894 MHz, 1850-1990 MHz, 1710-1755/2110-2155 MHz |               |        |         |         |
| Power output for single cell phone (Uplink) dBm   | 700MHz Band12/17                                                                           | 700MHz Band13 | 800MHz | 1700MHz | 1900MHz |
|                                                   | 23.9                                                                                       | 23.9          | 25.1   | 23.7    | 26.7    |
| Power output for single cell phone (Downlink) dBm | 700MHz Band12/17                                                                           | 700MHz Band13 | 800MHz | 2100MHz | 1900MHz |
|                                                   | 16.7                                                                                       | 16.8          | 16.9   | 16.8    | 16.8    |
| Noise Figure                                      | 5 dB nominal                                                                               |               |        |         |         |
| Isolation                                         | > 90 dB                                                                                    |               |        |         |         |
| Power Requirements                                | 120V AC 0.5A                                                                               |               |        |         |         |

Each Signal Booster is individually tested and factory set to ensure FCC compliance. The Signal Booster cannot be adjusted without factory reprogramming or disabling the hardware. The Signal Booster will amplify, but not alter incoming and outgoing signals in order to increase coverage of authorized frequency bands only. If the Signal Booster is not in use for five minutes, it will reduce gain until a signal is detected. If a detected signal is too high in a frequency band, or if the Signal Booster detects an oscillation, the Signal Booster will automatically turn the power off on that band. For a detected oscillation the Signal Booster will automatically resume normal operation after a minimum of 1 minute. After 5 (five) such automatic restarts, any problematic bands are permanently shut off until the Signal Booster has been manually restarted by momentarily removing power from the Signal Booster. Noise power, gain, and linearity are maintained by the Signal Booster's microprocessor.


The Manufacturer's rated output power of this equipment is for single carrier operation. For situations when multiple carrier signals are present, the rating would have to be reduced by 3.5 dB, especially where the output signal is re-radiated and can cause interference to adjacent band users. This power reduction is to be by means of input power or gain reduction and not by an attenuator at the output of the device.

ASSEMBLED IN THE USA



## Package Dimensions


27.5 L x 18 H x 6.5 W




FRONT



SIDE



TOP/BOTTOM



WEIGHT

MASTER CARTON: None

## Support



3 Year Warranty from Purchase

**Website:** [www.wilsonpro.com/support](http://www.wilsonpro.com/support)

**Phone:** +1 866 294 1660

Monday to Saturday

FOR PARTNER'S USE

UPC



460149-460150\_1300R\*1300\_SS\_US\_032221