



Model: **TXHTN3000** Intelligent Charger

Specifications

Voltage: The charger operates on the following voltage:

- U.S.A. /Canada: 120V AC, 60 HZ
- General market: 230V AC, 50/60 HZ

Temperature:

- Operating temperature 20° C ~ +45 ° C
- Storage temperature 20° C ~ +70 ° C

Charging Current: 800mA

Feature: This is a rapid charger.

ΔV , $\Delta Temp$, Maximum Voltage, Maximum Temperature and Maximum Charge Time cut off.

High PWM Charging Output to simplify the charging circuit with limited components.

Operation:

Plug the desktop charger into the DC line outlet.

Insert the battery pack into the charger. The display as follows:

Attention

a) When charging a battery pack alone (not attached to the transceiver), do not allow any metal object to short the terminals on the top of the pack.

b) The charger suitable for NiCd, NiMH Battery Pack. Lithium Battery is not workable.

Charging Mode

- Idle Mode.
- Front Trickle Charging Mode.
- Quick Charging Mode.
- Trickle Charging Mode.

Charge Status

LED Status

Power on
Test battery status in first 3 seconds
Charging
Charge completed
Battery Pack Take Off
Weak Battery Pack

Led Off
Green ON
Red ON
Green ON
Led Off
Yellow Flash

Approximate Charging Time

Battery Pack	Capacity		
HNN9008	7.5 V	1800 mAh	2.5 hours
HNN9009	7.5 V	2200 mAh	3.0 hours
HNN9013	7.4 V	2400 mAh	3.2 hours